PXR-93
Proximity Reader

Features

- Reliable & easy installation.
- Reader tamper proof detection function.
- Watchdog function secures system free from halting.
- Base on different demands, customs have different selection.
- Slim, stylish design, sensitive touch keypad with blue backlight suit for various locations.

(＊ Kindly refer to reader specification for more information.)

Ordering Information

Package Content : 1pc/inner box

- PXR-93 x1
- Plate x1
- Quick Start Guide x1
- Accessory Pack x1

Model No. Identification

P X R - 93 E S K L

- L: Auto Learning
- K: Keypad
- S: RS-485
- E: EM / M: MIFARE®
- 93: Device Type
- PXR: Product Category

Specifications

Model No.	PXR-93ET/EW (K)	PXR-93MT/MW(K)	PXR-93ES/ESK	PXR-93MS/MSK	PXR-93ESL/ESKL	PXR-93MSL/MSKL
	T2/Wiegand (125KHz)	T2/Wiegand (13.56MHz)	RS-485 (125KHz)	RS-485 (13.56MHz)	RS-485 L (125KHz)	RS-485 L (13.56MHz)
Processor	8 Bit					
Read Format	125 KHz (EM Compatible)	13.56 MHz (MIFARE®)	125 KHz (EM Compatible)	13.56 MHz (MIFARE®)	125 KHz (EM Compatible)	13.56 MHz (MIFARE®)
Read Range	8~10cm (max.)	3~5 cm (max.)	8~10cm (max.)	3~5 cm (max.)	8~10cm (max.)	3~5 cm (max.)
Keypad	12 Key (0-9, ＊, #)				13 Key (0-9, ＊, #, Bell)	
Input Ports	Case Sensor x 1 , LED Indicator control x 2 , Buzzer control x1		Case Sensor x 1		3 Sensors (Door Sensor x 1 、Exit Button x 1 、Case Sensor x 1)	
Output Ports	NONE				Relay x 1 (Door Lock)1 、O.C. Output x 2 (Door Lock/Alarm, external ACU-30/90)	
LED Indicator	Power / Comm.					
LCD Display	NONE					
RTC	NONE					
Beep Tone	Buzzer					
ID Setting	NONE		DIP switch setting			
Power Input	DC 12V / 1A					
Current Consumption	200mA (max)					
Comm. Interface	T1 / T2 / Wiegand		RS-485			
Comm. Baudrate	NONE		19,200 bps-N-8-1			
Operating Temp.	-10°C~ 55°C / 14°F~ 131°F					
Relative Humidity	20% ~ 80%(Non-condensing)					
Dimention(LxWxH)(mm)	120 x 77 x 22					
Weight(Device)	140g					

＊ Product design and specifications are subject to change without prior notice.