

Turbo 120

PLUS

With slowdown function in both opening and closing

Electronic and mechanical parts well protected from external agents.

With magnetic encoder for detecting obstacles with maximum safety.

With fixing plate included.

Possibility of speed and slowdown regulation

Stand by working

New generation batteries

For an intensive use

Possibility to integrate solar panel

NEW 900CT-724S, New self-programming control unit for 1 motor 24 Vdc

Provided with safety and LED command indication

Easy configuration with LCD display with 3 programming characters and 3 touches: easy menu for rapid installations, advanced menu for complex and customized installations

Flashing light , courtesy light and gate open light exit can be set up separately

Electronic protection to motor short-circuit, with rapid intervention

Electronic protection to overcharge

Accessories power exit can be deactivate from software to allow the energy saving modality

Self diagnosis through flashing light and display

New generation NI-MH batteries as optional on board

Electromechanical irreversible gear motor up to 1100 kg with new control unit 24 Vdc

DISPLAY
LCD

HI-TECH



CODE	DESCRIPTION
------	-------------

24V **900SC-110-24** 24 Vdc motor, control unit with slowdown, encoder, mechanical limit switch, for gates up to 1100 kg. With connectors for receiver. Intensive use

TECHNICAL FEATURES

		900SC-110-24
Control unit		900CT-724S
power	Vac (Vdc)	230 (24)
Consumption power	W	400
Motor consumption	A	2.3
capacitor	μ F	-
Protection degree	IP	44
torque	Nm	50
speed	m/s	0.23
Thrust force	N	900
Max gate weight	kg	1100
thermoprotection	$^{\circ}$ C	-
Working temperature	$^{\circ}$ C	-20 $^{\circ}$ +50 $^{\circ}$
weight	kg	11

GATES